



#P669
MODEL MP

UTG NEW GEN LOW PROFILE BI-DIRECTION CLAW MOUNT

MNT-P669

- Precision Machined from Aircraft-grade Aluminum Alloy for Maximum Strength
- Super Low Profile Design for Discreet and Stealthy Operations
- Clever Locking Clamp with Spring Retention for Quick and Easy Attachment
- Universal Bi-directional Design for Most MP5 and G3 Style Rifle Applications
- Matte Black Finish

NUM00901001



MNT-P669

#P669

MODEL MP

UTG NEW GEN LOW PROFILE BI-DIRECTION CLAW MOUNT

UTG NEW GEN LOW PROFILE BI-DIRECTION CLAW MOUNT INSTALLATION GUIDE

MNT-P669



1. Loosen the four M4 spring tension controlled locking screws on top with the bigger Allen wrench. Do not over loosen the screws.



2. Place the mount on top of the upper receiver. Slide it in position and make sure that the clamping plates are engaged with the notches on the upper receiver.



3. Press on the top rail, hold the clamping plates in position and evenly tighten the four locking screws with the bigger Allen wrench to secure the mount onto the upper receiver.



4. Optional Step - Adjust the two flat head screws on the top rail with the smaller Allen wrench for proper elevation compensation.

Caution: Make sure firearm is not loaded. Remove magazine and examine chamber. Use safe handling procedures at all times.



5. Install UTG CQB scope or other excellent quality UTG accessories to enhance shooting performance.