



# U416S MODEL 4/15

## CAR LENGTH QUAD RAILS

MTU001

- Precision Machined with Maximum Strength
- Four Mil-spec Picatinny Rails for Versatile Accessory Applications
- Simple and Friendly Installation, No Gunsmith or Tool Required
- Solid Locking Features for Most Secure Fit
- Ultimate Tactical Solution to Enhance Accuracy Under Toughest Environments
- Fits CAR Length Model 4, 15, 16 and Variants
- Hard Anodized Finish for Wear Resistance



MTU001

# U416S MODEL 4/15 CAR LENGTH QUAD RAILS

Made in USA


## MODEL 4/15 CAR LENGTH QUAD RAILS INSTALLATION GUIDE

MTU001

Caution: Make sure firearm is not loaded. Remove magazine and examine chamber. Use safe handling procedures at all times.



1. Use a handguard removal tool to pull down the Delta Ring and remove the handguards.



2. Separate the metal quad rails (covers) into 2 pieces, the Top Cover (3 rails) and the Bottom Cover (1 rail). Install the Top Cover onto the barrel by aligning the inner two spinal cords against the central groove area on the Barrel Nut, and push for a tight fit.



3. Press downward the Top Cover to pull back Delta Ring, and then release toward the barrel to allow the Front Handguard Cap to fit snugly inside the front rim of the Top Cover. Make sure that the Top Cover is well situated.



4. Repeat step 3 for the Bottom Cover installation.



5. Tighten all four screws using the provided Allen wrench to secure the top and bottom covers. The Quad-rail is ready for most versatile accessory applications.




TOP COVER


BOTTOM COVER



CENTRAL GROOVE AREA



FRONT HANDGUARD CAP



CORRECT INSTALLATION